

Frenzy-S 1x17x20 Red Dot Sight MRT Aspheric Lens EDC

Model: SCRD-M68




The advanced aspheric lens design ensures crisper, sharper images with minimal distortion. Unlike bulkier spherical lenses, the thinner profile of aspheric lenses enables a lightweight and streamlined design.

- Multi Reticle, 3 MOA Dot, Crosshair and Circle Plus 9 Brightness & 2 NV Illumination Mode for Diverse Shooting Scenarios
- Aspheric Lens Minimize the Aberration & Free of Distortion, 26 g / 0.92 oz Lightweight Design for EDC (Every Day Carry)
- Motion Sensor No Worry to Forget to Switch Off the Sight, Battery Side Loading for Easy Replacement Without Losing Zero
- 7075-T6 Aluminum Alloy Ensures Durability, IP67 Waterproof Enclosed Design Allows to Use in All Weather Conditions

It can withstand physical shocks, impacts or vibrations, guaranteeing red dot sights and remains accurate and reliable even after prolonged use in rugged conditions.



Frenzy-S 1x17x20 Red Dot Sight MRT Aspheric Lens EDC



3 MOA Dot Size
Popular Size to Balance Precision and Speed



Multi-Reticle
Dot Reticle, Crosshair Circle and Crosshair Circle with Dot Reticle



NV-Compatible Illumination
NV Illumination for Taking Shot at Night



Side-load Battery Tray
Change Battery without Re-zero



Motion Sensor
Effortless Activation and Battery Savings



7075-T6 Aluminum Alloy Housing
Ultra-lightweight, Stable and Durable



Close Self-defence
Design for Close-range Self-defense Aiming



Parallax Free
Point of Aim Aligns with Point of Impact

Frenzy-S 1x17x20 Red Dot Sight MRT Aspheric Lens EDC

Model: SCRD-M68

Window Lens Size/ Objective Lens Size	17x20 mm / 0.67x0.79 in
Eye Relief	N/A
Parallax	≤ 2 MOA
Parallax Setting	33 yards
Dot Size / Reticle	3 MOA Dot, Circle, Crosshair, etc
Dot/ Reticle Color	Red

Sensor	Motion Sensor
Click Value	1 MOA
Elevation Adjustment Range	≥ 90 MOA
Windage Adjustment Range	≥ 90 MOA
Footprint	MGT
Mounting Rail	Weaver
Illumination Setting	9 Daylight & 2 Night Vision
Battery Type	CR1620
Battery Life	Up to 50,000 hours (Lowest Power Mode)
Battery Placement	Side Loading
Waterproof	IP67
Shockproof	1500 G
Working Temperature	-20~+60° C / 2H
Housing Material	7075-T6 Aluminum Alloy
Mount Material	6061-T6 Aluminum Alloy
Finish	Matte Black
Weight (without mount)	26 g / 0.92 oz
Items in the Package	User Manual, Cleaning Cloth, Vekey, Weaver Mount, Hex Keys, etc.

Frenzy-S 1x17x20 Red Dot Sight MRT Aspheric Lens EDC

Model: SCRD-M68

